

Full Automatic Multi Needle Chain Stitch Quilting Machine (With Slitters)



*Thanks to blades on the Xmovement section, the borders are slitting between two patterns accurately, and also the possibility of patterning with a 1/2" (half inch) needle.

*Explanation of the press arrangement with the air pressure device.

*New tip frame structure with low show.

*Optimized mechanical structure provides higher speed and more production.

*Practical patented product makes its "moving needle" quilting patterns more elegant.

*Firmer thread stitches take the quilting pattern to stronger dimensions.

*The needle bar and its attacks are controlled by a double swinging device, avoiding lubrication and sewage.

*Multiple interval and independent patterns (360-180 degree patterns available.)

*Rope break sensors allow the machine to stop automatically in case of upside down or yam breakage. It also allows personnel to navigate the front and rear safety machines.

TECHNICAL SPECIFICATIONS (MM)

Size (L x W x H) : 4795 × 1670 × 2050

Quilting Width : 2450

Space Between Needle Rows : 50.8,76.2,127 (5 ")

Space Between Needle Rows : 76.2,76.2,152.4 (6 ")

Space Between Needles : 12.7

X-Axis Movement Displacement : 410

Thickness of Quilting : ≤ 80

Stitch Leng : 3-8

Speed of Operation : 60 ~ 300 (m / hour)

Model of Needle : 24/180 23/160 22/140 21/130

Quilting Speed : 600 -1200 (rpm)

Total Power Required : 7KW

Voltage : 380V / 50Hz 220V / 60Hz

Gross Weight : 5000kg

Slitting Width :100-400

