

SX-100 DIGITAL SPRING COILING MACHINE



TECHNICAL PARAMETERS

| | |
|--------------------|--|
| Spring Type: | Bonnel |
| Capacity: | 90-95 pcs/min |
| Spring End Ring: | Ø62-Ø95mm |
| Steel Wire Gauge: | Ø2.0 -Ø2.4 mm (<Ø2.0mm on request) |
| Spring Height: | 70-190mm (190-210mm on request) |
| Convolutions: | 4-7 Turns |
| Main Drive Power: | 4 KVA |
| Swift Frame Power: | 2.2 KVA |
| Heat Treatment: | 10 KVA |
| Weight: | Net Approx. 2730 KG |
| Power Requirement: | 380V 3Phase, 50-60Hz (415V - 480V - 220V optional) |

- The factory reserves all rights to change product specifications without any information.

- The machine will be adjusted to a spring size within the range specified in its technical specifications.

- Each additional modification of the actual coil specification may request additional tools.

- It produces spiral shape springs from the form of a wire.

- There is a touch screen system indicated by symbols.

- Error warnings are in English and also other languages are possible upon a requested.

-The materials used are products of internationally known brands. For example; Delta, SMC Pneumatic, Panasonic Sensor, Bauer Sensor)

- The machine is CE certified.

- One year guarantee for the manufacturing fault

