

SX-700D HIGH SPEED POCKET SPRING ASSEMBLER



- It produces a spring carcass to the assembly machine with automatic transfer system from the form of a wire into a spiral shape without human touch.

- When the unit is finished, it automatically turns on a new unit. Nodes and wire drive are server controlled.

- There is a quality control system at every production step of the spiral.

- There is a touch screen system indicated by symbols.

- The materials used are products of internationally known brands. For example; Delta, SMC Pneumatic, Panasonic Sensor, Bauer Sensor)

- Error warnings are in English and also other languages are possible upon a requested.

- The machine is CE certified.

- One year guarantee for the manufacturing fault

TECHNICAL PARAMETERS

Spring Type:	Barrel or Cylinder
Spring Core Width:	< 2200 MM
Capacity:	30+ Rows/Min
Spring Waist Ext Dia:	Ø37-Ø75mm,
Pocket Haight:	55-240MM
Fabric Thickness:	> 60 G/M2
Fabric Width:	< 2300 MM
Main Drive Power:	25 KVA
Air Consumption:	12 M3/H
Weight:	7080 KG
Power Requirement:	380V 3Phase , 50-60Hz (415V - 480V - 220V opsiyonel)

- Work with 5-6 coilers
- With or without upper and lower fabric
- Capacity: 30+ Rows/Min
- 6 glue are possible
- The factory reserves all rights to change product specifications without any information.
- The machine will be adjusted to a spring size within the range specified in its technical specifications.

- Each additional modification of the actual coil specification may request additional tools.

